

METROPOLITAN MATERIALS

RENTAL

6581 Metro Parkway

Sterling Heights MI

586.264.3370

PRODUCT & INFORMATION

DINGO TX 1000 WIDE TRACK

- Loader arm design increases load capacity and greater reach at full height
- Rated operating capacity over 1,000-lbs
- 81" (206 cm) hinge pin height easily clears side of a 30yard dumpster or one-ton truck for maximum jobsite productivity
- Exclusive traction control design is intuitive, easy to operate, and effortless
- Bucket/Forks available







DINGO ATTACHMENTS

Auger & 9" & 12" Bit

- •Designed for large auger bits up to 30" (76cm)
- •High Torque (Power) Drive for the most demanding conditions
- Direct planetary drive





Forks

- Easily adjustable width
- •High strength steel forks
- Excellent for carrying materials on jobsites

Breaker

- Multi-position mounting head
- •Powerful, 180 ft-lbs. (244 N) of force
- Variety of bits available



WHITEMAN WBH-21EF

- Payload capacity 21 cubic foot
- Maximum load capacity 3200 Lbs.
- High density polyethylene tub will withstand the toughest use
- 18 Horsepower Vanguard engine
- Starting system recoil and electric start
- Travel speed: 7.25 mph
- Large fuel capacity 4.8 gallon for uninterrupted operation
- Superflex foam filled tires provide a soft air-like ride while extending tire life





TRACK/PIVOT DUMP -CANDYCOM

- Payload capacity 16 cubic foot
- Length x Width x Height (in.)
 Dump)
- Speed (mph)
- Weight (lbs.)
- Engine
- Transmission
- Rubber Tracks
- 90 Dump Angle

106 x 35 x 54 (Straight) 108 x 35 x 54 (Pivoting)

0-6

1,521 (Straight Dump)

1,631 (Pivoting Deck)

690 CC Honda Gas Engine

Hydrostatic





TAMARACK CB-1600

- Payload capacity 16 cubic foot
- Maximum load capacity 2500 Lbs.
- Retractable Standing Platform
- 13 Horsepower Honda engine
- Starting system recoil and electric start
- Travel speed: 7 mph
- Large fuel capacity 4 gallon for uninterrupted operation
- Superflex foam filled tires provide a soft air-like ride while extending tire life





ALLEN AW16-H

• Engine: Honda: GX390

Horsepower: 13 hp

Starter recoil or electric

• Fuel Type: Gasoline

• Fuel Capacity: 1.7 gal

• Top Speed: 7 mph

• Payload: 2,500 lb

• Bucket Capacity: 16 cu. ft.

• Lift cylinder diameter: 2 in

• Dump angle: 90º

• Dump / return speed empty: 5 seconds

• Wheelbase: 40 in

Foam filled tires

• Weight: 1,365 lb

• Dimensions (l x w x h): 97" x 47" x 50"





5x10 SCISSOR LIFT TRAILER w/ 3500LB AXLES

Manufacturer: BND

• Floor Length: 5' or 60.00"

• Width: 10' or 120.00"

• Weight: 1960 lbs

• GVWR: 7000 lbs

• Payload Capacity: 5040 lbs

• Axle Capacity: 3500 lbs





GROUND THAW TRAILER

Maximum Filled Weight

Boiler

Fuel Capacity

Heat Transfer

Fluid Reservoir

Hose Length

Hose Rating

Electrical Requirements

Trailer

4,800 lbs

329,000 BTU

120 US gals

Propylene Glycol/Water

78 US gals

(3) 1000ft loops

200 PSI

30 amp, 120V

6×12 Tandem Axel





6X10 AMERICAN HIGH SIDE TRAILER

• Model: 6 x 10

• Floor Length: 10' or 120.00"

• Width: 6' 4" or 76.00"

• Weight: 826 lbs

• GVWR: 3500 lbs

• Payload Capacity: 2674 lbs

• Flat 4 wire plug

Radial 15 inch tires

• 2 in coupler

• 4 foot gate

• 1 foot side railings

• 5/4 treated deck boards





4 X 8 BLACK GROUND PROTECTION MAT

- Infused with rubber for superior grip & flex
- Lightweight and easy to transport
- Easy to install on uneven surfaces
- Reduce cleanup time
- Protect vegetation and plants
- Prevent rutting and runoff
- Eliminate the need for gravel
- Include hand holes for easy placement & storage





SENCORE S8100 SAW

- No more mixing oil and gas Auto Lube Technology electronically mixes oil and fuel from two separate tanks
- No manual choke electronically controlled choke means hot or cold starting is equally easy.
- Knocking the dust out of the air filter external rocker wheel vibrates the impurities from the air filter without opening the air box
- Multi-stage filter means only pre-filtered air will reach the main filter
- 81cc two-stroke German engine with 23.1 lbs. total weight
- Lightweight and high power with optimum weight distribution
- steel-sprung anti-vibration system
- Easily serviceable throughout the life of the saw
- Engine block is replaceable through the removal of a few bolts
- 20mm shaft with a removable 1" bushing
- Water supply connection





HILTI HAMMER DRILL

- •High versatility for a wide range of drilling and chiseling applications
- Exceptionally high performance-to-weight-ratio
- •Active Vibration Reduction (AVR) makes the tool less tiring to use helping to increase daily productivity
- •Drilling anchor and through-holes in concrete and masonry





4000W LED LIGHT TOWER/GENERATOR

- Full tubular steel frame trailer
- •30' foot all-steel mast
- •68" Broad-based design for stable transport in rough terrain
- •4 -1,000 watt metal halide lights
- •4 point outrigger stance withstands 65+ mph winds
- •4-stroke diesel engine
- Marathon generator
- •Low oil/high temperature automatic shutdowns
- Protective start limit breaker
- •Individual light breaker switches
- •New ballast function with centralized diagnostic capability inside control box





MINI EXCAVATOR

- •Cat® C1.1 Turbo Engine (U.S. EPA Tier 4 Final/EU Stage V)
- Automatic Engine Idle
- Automatic Engine Shutdown
- Automatic Two Speed Travel
- •Fuel Water Separator
- Power on Demand (not available in all regions)
- Variable Displacement Piston Pump
- Load Sensing/Flow Sharing Hydraulics
- •Smart Tech Electronic Pump
- Accumulator
- Automatic Swing Brake
- Auxiliary Hydraulic Lines
- One and Two Way Auxiliary Flow
- Continuous Auxiliary Flow
- Auxiliary Line Quick Disconnects
- •2 Bucket Sizes 12" & 18"





18' X 6' BEHNKE TILT TRAILER

• 4'ft Stationary with 14'ft Tilt Deck

• 2-7k Axles

• Weight: 3100 lbs

• GVWR: 14000 lbs

Payload Capacity: 10900 lbs





16' NOVAE TRAILER

• Model: 82' x 16'

• Floor Length: 14' or 168.00"

• Width: 6' 10" or 82.00"

• Weight: 2210 lbs

• GVWR: 9900 lbs

Payload Capacity: 7690 lbs

Axle Capacity 5198 lbs





2016 CAT 259D SKID STEER

Dump Angle: 52 Degrees

Overall Track Length: 6.56FT

• Engine Model: Cat C3.3B

• New Power: 73.2 hp

• Peak Torque: 195.5FT

Operating Weight: 8847.2lb

• Operating Load: 2899.1lb



